

## High Led Power


(28,42,56,70,84,98,100,120,140,154,168,182,196)  
Watt



<b>POWER</b>	28 W	42 W	56 W	70 W	84 W
<b>VOLTAGE</b>	DC12/24/48V-220vac	DC12/24/48V-220vac	DC 12/24/48V-220vac	DC12/24/48V-220vac	DC12/24/48V-220vac
<b>LUMINOUS FLUX</b>	100-120 lm/w	100-120 lm/w	100-120 lm/w	100-120 lm/w	100-120 lm/w
<b>COLOUR TEMP.</b>	3500-5000K	3500-5000K	3500-5000K	3500-5000K	3500-5000K
<b>CRI</b>	>70	>70	>70	>70	>70
<b>WORKING LIFE</b>	50000 H	50000 H	50000 H	50000 H	50000 H
<b>SIZE</b>	590*425*155 mm	596*425*155 mm	602*425*155 mm	608*307*80 mm	614*307*80 mm
<b>PF</b>	>0.9	>0.9	>0.9	>0.9	>0.9
<b>WARRANTY</b>	1 Year	1Year	1Year	1Year	1 Year
<b>BODY MATERIAL</b>	Compressed Aluminum	Compressed Aluminum	Compressed Aluminum	Compressed Aluminum	Compressed Aluminum
<b>IP</b>	IP 66	IP 66	IP 66	IP 66	IP 66
<b>BEAM ANGLE</b>	120°	120°	120°	120°	120°



<b>POWER</b>	<i>98 W</i>	<i>100 W</i>	<i>120 W</i>	<i>140 W</i>	<i>154 W</i>
<b>VOLTAGE</b>	<i>DC12/24/48V-220vac</i>	<i>DC12/24/48V-220vac</i>	<i>DC12/24/48V-220vac</i>	<i>DC12/24/48V-220vac</i>	<i>DC12/24/48V-220vac</i>
<b>LUMINOUS FLUX</b>	<i>100-120 lm/w</i>	<i>100-120 lm/w</i>	<i>100-120 lm/w</i>	<i>100-120 lm/w</i>	<i>100-120 lm/w</i>
<b>COLOUR TEMP.</b>	<i>3500-5000K</i>	<i>3500-5000K</i>	<i>3500-5000K</i>	<i>3500-5000K</i>	<i>3500-5000K</i>
<b>CRI</b>	<i>&gt;70</i>	<i>&gt;70</i>	<i>&gt;70</i>	<i>&gt;70</i>	<i>&gt;70</i>
<b>WORKING LIFE</b>	<i>50000 H</i>	<i>50000 H</i>	<i>50000 H</i>	<i>50000 H</i>	<i>50000 H</i>
<b>SIZE</b>	<i>620*300*50 mm</i>	<i>680*300*50 mm</i>	<i>740 *300*50 mm</i>	<i>800*300*50 mm</i>	<i>806*300*50 mm</i>
<b>PF</b>	<i>&gt;0.9</i>	<i>&gt;0.9</i>	<i>&gt;0.9</i>	<i>&gt;0.9</i>	<i>&gt;0.9</i>
<b>WARRANTY</b>	<i>1 Year</i>	<i>1Year</i>	<i>1Year</i>	<i>1Year</i>	<i>1 Year</i>
<b>BODY MATERIAL</b>	<i>Compressed Aluminum</i>	<i>Compressed Aluminum</i>	<i>Compressed Aluminum</i>	<i>Compressed Aluminum</i>	<i>Compressed Aluminum</i>
<b>IP</b>	<i>IP66</i>	<i>IP66</i>	<i>IP66</i>	<i>IP66</i>	<i>IP66</i>
<b>BEAM ANGLE</b>	<i>120°</i>	<i>120°</i>	<i>120°</i>	<i>120°</i>	<i>120°</i>



<b>POWER</b>	<i>168 W</i>	<i>182 W</i>	<i>196W</i>
<b>VOLTAGE</b>	<i>DC12/24/48V-220vac</i>	<i>DC12/24/48V-220vac</i>	<i>DC12/24/48V-220vac</i>
<b>LUMINOUS FLUX</b>	<i>100-120 lm/w</i>	<i>100-120 lm/w</i>	<i>100-120 lm/w</i>
<b>COLOUR TEMP.</b>	<i>3500-5000K</i>	<i>3500-5000K</i>	<i>3500-5000K</i>
<b>CRI</b>	<i>&gt;70</i>	<i>&gt;70</i>	<i>&gt;70</i>
<b>WORKING LIFE</b>	<i>50000 H</i>	<i>50000 H</i>	<i>50000 H</i>
<b>SIZE</b>	<i>812*300*50mm</i>	<i>818*300*50 mm</i>	<i>824*300*50 mm</i>
<b>PF</b>	<i>&gt;0.9</i>	<i>&gt;0.9</i>	<i>&gt;0.9</i>
<b>WARRANTY</b>	<i>1 Year</i>	<i>1Year</i>	<i>1Year</i>
<b>BODY MATERIAL</b>	<i>Compressed Aluminum</i>	<i>Compressed Aluminum</i>	<i>Compressed Aluminum</i>
<b>IP</b>	<i>IP 66</i>	<i>IP 66</i>	<i>IP 66</i>
<b>BEAM ANGLE</b>	<i>120°</i>	<i>120°</i>	<i>120°</i>