



	Solar LED Flood Light (50	0 W) Model : SP2-0101
Solar Panel	Max Power	6V 7W, Polycrystalline
	Life Time	25 Years
Battery	Туре	Life PO4 32650 3.2v 12AH Battery
	Life Time	5-10 Years
LED Lamp	Max Power	12V 50W
	LED Chip Brand	Bridgelux
	Lumen (LM)	1300lm
	Life Time	50000 Hours
	Viewing Angle	120°
Charge Time	By Sun	6-8 Hours (with Enough Strong Shine)
Discharge Time	Full Power	More 10 Hours
Discharge Time	Saving Mode	More 30 Hours
Working Temperature	Range (C)	-30´C – 70´C
Color Temperature	Range (K)	3000-6500K
Mounting Height	Range (M)	3-5m
Space Between Light	Range (M)	9-13m
Main Material Of Lamp	ABS	
Certificate	CE Rohs	
Warranty Period	2 Years	
Packing & Weight	Product Size	250 *190 *100mm
	N.W/G. W.	15 KG
	Carton Size	570*430*230 mm
	Q'ty/CTN	6 Pcs/CTN





	Solar LED Flood Light (100 W) Model : SP2-0102
Solar Panel	Max Power	6V 8.5W , Polycrystalline
	Life Time	25 Years
Battery	Туре	Life PO4 32650 3.2v 18AH Battery
	Life Time	5-10 Years
LED Lamp	Max Power	12V 100W
	LED Chip Brand	Bridgelux
	Lumen (LM)	1800lm
	Life Time	50000 Hours
	Viewing Angle	120°
Charge Time	By Sun	6-8 Hours (with Enough Strong Shine)
Disabarga Tima	Full Power	More 10 Hours
Discharge Time	Saving Mode	More 30 Hours
Working Temperature	Range (C)	-30´C – 70´C
Color Temperature	Range (K)	3000-6500K
Mounting Height	Range (M)	4-6m
Space Between Light	Range (M)	11-15m
Main Material Of Lamp	ABS	
Certificate	CE Rohs	
Warranty Period	2 Years	
Packing & Weight	Product Size	280 * 250 * 100 mm
	N.W/G. W.	15 KG
	Carton Size	610*420*295 mm
	Q'ty/CTN	6 Pcs/CTN





5	Solar LED Flood Light (150 W)	Model : SP2-0103
Solar Panel	Max Power	6V 12W , Polycrystalline
	Life Time	25 Years
Battery	Туре	Life PO4 32650 3.2v 24AH Battery
	Life Time	5-10 Years
LED Lamp	Max Power	12V 150W
	LED Chip Brand	Bridgelux
	Lumen (LM)	2100lm
	Life Time	50000 Hours
	Viewing Angle	120°
Charge Time	By Sun	6-8 Hours (with Enough Strong Shine)
Discharge Time	Full Power	More 10 Hours
	Saving Mode	More 30 Hours
Working Temperature	Range (C)	-30´C – 70´C
Color Temperature	Range (K)	3000-6500K
Mounting Height	Range (M)	5-8m
Space Between Light	Range (M)	13-19m
Main Material Of Lam	o ABS	
Certificate	CE Rohs	
Warranty Period	2 Years	
	N.W/G. W.	24 KG
Packing & Weight	Carton Size	760*420*295 mm
	Q'ty/CTN	6 Pcs/CTN